


PN16 DIN-3202

SIZE VALVE	L1	L2	B	D	T	R	F	C	H	N	H1	H2	K	□	A	G	KG	
25	1	180	90.0	24	115	16	68	1	85	14	4	103	30	75	12.0	M6	50	9.5
40	1 1/2	200	100.0	39	150	16	88	2	110	18	4	133	50	235	16.0	M8	70	13.0
50	2	220	110.0	49	165	18	102	2	125	18	4	136	50	235	16.0	M10	70	17.0
65	2 1/2	250	125.0	63	185	18	122	2	145	18	4	146	53	340	19.5	M10	102	27.0
80	3	260	130.0	74	200	20	138	2	160	18	8	156	53	340	19.5	M10	102	29.0
100	4	340	170.0	100	220	20	158	2	180	18	8	172	50	340	19.5	M10	102	45.0
150	6	455	227.5	150	285	22	212	2	240	22	8	236	72	510	25.0	M12	125	103.0

POWER TYPE	A	B	C	D
L 型				
T 型				
T 型				



### FEATURES

- \* The flange ends conform to ANSI B16.5
- \* Multiport design
- \* Investment casting
- \* PN16, full port
- \* Unique one piece ball and stem design (TRUNION BALL)
- \* ISO5211 Mounting pad
- \* Anti-Static Device
- \* Fire safe design
- \* Blow-out proof stem

NO.	NAME OF PARTS	MATERIAL			
1	BODY	CAST IRON	WCB	ASTM A351CF8	ASTM A351CF8M
2	BALL SEAT	PTFE	PTFE	PTFE	PTFE
3	BALL WITH STEM	CF8	CF8	CF8	CF8M
4	SEAT RING HLODER	CAST IRON	CAST IRON	CF8	CF8M
5	O RING	O RING	O RING	O RING	O RING
6	RETAINER	CAST IRON	CAST IRON	CF8	CF8M
7	STEM PACKING	PTFE	PTFE	PTFE	PTFE
8	GLAND FLANGED	CAST IRON	CAST IRON	CF8	CF8M
9	GLAND BOLT	SS41	SS41	SUS304	SUS304
10	TOP COVER	CAST IRON	CAST IRON	CF8	CF8M
11	JOINT GASKET	PTFE	PTFE	PTFE	PTFE
12	STEM	CF8	CF8	CF8	CF8M
13	HANDLE	CAST IRON	CAST IRON	CAST IRON	CAST IRON

	DESC	3-WAY BALL VALVES FLANGED ENDS-FULL PORT	DRAWING #	ETG-3WFLCI/16 ETG-3WFLSS/16	
	APPROVED BY.		DATE	2010/07/14	
	DRAWER	<i>Y. J. Lee</i>	MATERIAL		MODIFICATION